

19" Panel PC IP65 foran, Celeron, I5 eller I7, 2xCOM, 2xRJ45, 9~36Vdc, 10Bit GPIO, FEATURES

19" TFT-LCD Panel PC
IP65 foran
Oppløsning: 1280*1024
250 nits
5-leder resistiv berøringsskjerm (kapasitiv berøring på forespørsel)
Intel Celeron J4125/J6412 CPU / Core i5 /i7
RAM: 1x SO-DIMM DDR4 (celeron) maks 16 GB, i5/i7 2x SO-DIMM DDR4 maks 32 GB
1 x M.2 2242/2260/2280 SATA
1 x SATA (2,5" SATA)
1 x M.2 2280 NVME
MPCle: M.2 3042/3052 for 3G/4G/5G med innebygd SIM-spor, M.2 2230 WiFi & BT
2x RJ45 Intel i225V (på spesiell forespørsel kan 2 til legges til)
USB: Celeron versjon: 4*USB2.0+2*USB3.0 (J4125/J6412), i5/i7 versjon 4*USB3.0+2*USB2.0
COM: 2x DB RS-232/422/485-port, 4*RS232 i utvidelsesport
GPIO: 1* 10 bit GPIO Inne i utvidelsesporten
Strømforsyning: 9-36V DC plugg
Arbeidstemperatur: Med luftstrøm -10 ~ 60° C
Antivibrasjon med SSD: 3 Grms, IEC 60068-2-64, tilfeldig, 5 ~ 500 Hz, 1 time/akse
Anti-sjokk med SSD: 30 G, IEC 60068-2-27, halv sinus, 11 ms varighet
437,27 x 361,27 x 68,8 mm
OS-støtte: Windows 10 / Ubuntu, CentOS



SPECIFICATIONS

Memory Type	:	DDR4
Max. Memory Capacity	:	16
Power Input	:	DC 9~36V
Antal Video Udgange	:	1
Antal LAN Porte	:	2
Antal USB	:	6
Antal Serial	:	2

