

MON21.5-T-IP69K

21,5" IP69K rustfri PCAP-chassismonitor for mat- og kjemisk industri, alternativ 1000 nits

FEATURES

21,5", FULL HD 1920 x 1080 16,7 m farger
Lysstyrke 250 nits (mulighet: 1000 nits)
IP69K
VGA, (mulighet HDMI)
USB for berøringsskjermkontroll
PCAP Projisert kapasitiv multitouch-skjerm,
berøring med flat design
En ekte flat, lett å rengjøre frontflate med kant-
toedge-design
Full IP69K vanntett kabinett
SUS 316/ AISI 316 rustfritt stål for næringsmiddel-
og kjemisk industri
Vanntett forseglet kanalrør for kabelbeskyttelse
Støtt VESA / YOKE-feste
Optisk binding (mulighet)
Driftstemperatur 0°C til 45°C
541 x 337 x 56,2 mm
12V DC



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

USB	:	1x USB typeA for touch screen control
Driftstemperatur	:	0°C to 45°C
Approval	:	CE, FCC
Forsyning	:	12V DC
IP-Tæthed	:	IP rating Full IP65/IP69K
Kontrast	:	3000:1
Luftfugtighed	:	10% to 90% RH, NonCondensing
Maks. opløsning	:	1920 x 1080
Materiale	:	Stainless Housing
Montering	:	Vesa; Yoke
Touch	:	Projected Capacitive Multi Touch Screen
VGA	:	1



**DANBIT**

MON21.5-T-IP69K

SPECIFICATIONS

Dimensioner : 541 x 337 x 56.2 mm



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.