

12,1" vifteløs panel PC IP65 front12,1" LCD-skjerm,
1280 x 800, LED 400 nits, Intel® Celeron J6412
widescreen

FEATURES

12,1" LCD 1280 x 800 LED 400 nits
Intel® Celeron J6412-prosessor Intel® Elkhart Lake
BISO UEFI
Støtte DDR4-2666/2933/3200MHz, maks. Kapasitet
32GB
2 x HDMI
3 x USB 3.0
3 x USB 2.0
2 x LAN
1 x Line-out
1 * M.2 Key-M(NVMe SSD 2280), 1 * M.2 Key-B-spor
Sikkerhetsstøtte TPM 2.0 innebygd IC
Standard IP66/IP67-modeller I/O: 1 x HDMI, 2 x
USB, 1 x LAN.
(Må bestilles spesielt: koblingstype: M12
metallkontakter, MIL-38999, MIL-26482 serie
kontakter
-15°C ~ 70°C (5°F ~ 158°F), 10% ~ 90% (ingen
kondens)



SPECIFICATIONS

Memory Type	:	DDR3
Max. Memory Capacity	:	32
Power Input	:	DC 12V
Antal Video Udgange	:	2
Antal LAN Porte	:	2
Antal USB	:	6

