

Wi-Fi 6 AX1800 dobbeltbånds VPN-sikkerhetsruter med option PoE+

FEATURES

- Neste generasjons Wi-Fi 6 (802.11ax) med hastigheter opptil 1,8 Gbps
- Dobbeltbånd (2,4 GHz og 5 GHz) med MU-MIMO for miljøer med høy tetthet
- Robuste VPN-funksjoner: IPSec, SSL, PPTP, L2TP, GRE (opptil 60 tunneler)
- Innebygd SPI-brannmur, DoS/DDoS-beskyttelse, innholds- og IP-filtrering
- Dobbelt WAN med failover, lastbalansering og støtte for høy tilgjengelighet
- Sentral AP-kontroller med captive portal og RADIUS
- Option** PoE+-versjon med 4-porters 802.3at PoE og PD Alive Check
- Enkel distribusjon via oppsettveiviser, dashbord og fjernadministrasjon



SPECIFICATIONS

Driftstemperatur	:	0°C to 50°C; fanless design
Annen	:	Built-in AP controller with captive portal and RADIUS
Firewall	:	SPI Firewall, DoS/DDoS protection, NAT, MAC/IP filtering, Content Filtering, WPA3 support
Porte	:	5 x Gigabit RJ45 (1 WAN, 1 LAN/WAN, 3 LAN)
Standarder	:	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), dual-band 2.4GHz + 5GHz
Material	:	Metal housing, 1U height, desktop or rack-mountable
WiFi	:	Up to 600Mbps (2.4GHz) + 1200Mbps (5GHz)
WWAN	:	Dual-WAN failover, load balancing, high availability

