

ATX-hovedkort med Intel® Core™ Ultra CPU, W880-brikkesett

FEATURES

Støtter Intel® Core™ Ultra CPUer, LGA 1851-sokkel
Opptil 192 GB DDR5 UDIMM ECC/ikke-ECC-minne
Integrert Intel® UHD-grafikk som støtter fire skjermer (VGA, 2x DP++, HDMI)
Utvidelsesspor: 2x PCIe x16 (Gen5), 4x PCIe x4, 1x PCI, 2x M.2 M-nøkkel, 1x M.2 A-nøkkel, 1x M.2 E-nøkkel
LAN: 3x 2,5 GbE, 1x 1 GbE (RJ45)
6x COM-porter (2x RS232/422/485, 4x RS232)
USB-porter: 4x USB 3.2 Gen2, 6x USB 3.2 Gen1, 3x USB 2.0
4x SATA III (RAID 0/1/5/10 støttes)
Lyd: Linjeutgang, mikrofoninngang, linjeinngang (valgfritt), Realtek ALC888S-kodek
8-bit GPIO (4 inn/8 ut)
Driftstemperatur: -5 °C til 65 °C
Mål: ATX-formfaktor (305 x 244 mm)
ATX-strømkontakt (24-pinn + 8-pinn)



SPECIFICATIONS

CPU	:	Intel® Core™ Ultra, LGA 1851
USB	:	4x USB 3.2 Gen2, 6x USB 3.2 Gen1, 3x USB 2.0
Serial	:	6x COM (2x RS232/422/485, 4x RS232)
LAN	:	3x 2.5GbE, 1x 1GbE
Driftstemperatur	:	-5°C to 65°C
Forsyning	:	ATX (24-pin + 8-pin connectors)
GPIO	:	8-bit digital I/O (4-in/8-out)
Grafik	:	Integrated Intel® UHD Graphics, Quad display support (VGA + 2x DP++ + HDMI)
Lyd	:	Realtek ALC888S Codec (Line-out, Mic-in, optional Line-in)
SATA	:	4x SATA III (RAID 0/1/5/10)
Udvidelser	:	2x PCIe x16 (Gen5, x16 or x8/x8) 4x PCIe x4 (Gen4/5) 1x PCI 2x M.2 M-Key (PCIe NVMe) 1x M.2 A-Key (for OOB) 1x M.2 E-Key (Wi-Fi/CNVi)
Certificate	:	CE, FCC Class B, RoHS, UKCA



**DANBIT**

BK1851-W880

SPECIFICATIONS

Dimensioner : ATX Form Factor (305 x 244 mm)



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.