

ETHIO3I40-I

2 x Analog til lastcelle, +/- 2.5V, 0-20mA, 1 x Eksitasjon till celle, 2x digital zoom, 2 x Digital Output (OC). LAN

FEATURES

2 stk. analog indgange samt 1 analog og 2 digital indgange



Danbit A/S Schous plass 1 Oslo, N-0552
Norway



67 104 460



salg@danbit.dk

SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 5,3 W via klemrække
Indgang	:	2 stk. analoge differentialindgange: ± 15 mV, ± 50 mV, ± 100 mV, ± 500 mV, ± 1 V, $\pm 2,5$ mV, 0 - 20mA, 4 - 20mA og ± 20 mA
Indgang	:	2 stk. digitale: Logisk 0: 0-1 VDC og Logisk 1: 3,5-50 VDC
Netværk	:	10/100 Mbit m/RJ45-stik
Protokol	:	Modbus/TCP, TCP/IP og UDP
Software	:	Leveres med konfigureringssoftware til Windows 2000, XP, Vista, WIN7/8/10
Tæller	:	Digitale Indgange kan virke som 32 bit tæller, maks. frekvens 100 Hz
Udgange	:	2 x Isolated Open Collector, 700 mA/Channel, +5 VDC ~ +50 VDC

