

I775-Q35

Eldre CPU-kortsokkel LGA775 CPU PICMG 1.3 Q35-  
brikkesett, WINDOWS 2000, XP, VISTA, Windows 7-  
støtte IB935

## FEATURES

Q35 brikkesett Core 2 Quad/ CORE 2 DUO / Celeron  
400 sekvensprosessor (conroe-L)  
LGA 775 FSB 800 / 1066 / 1333 MHz  
2 x Gigabit Lan, (Intel 82566DM, Intel 82574L)  
VGA (GMA 3100), CRT-støtte  
SATA II  
Parallellport LPT  
2 x COM  
4X USB 2.0  
OS-STØTTE: Windows 2000, Windows XP, Windows  
VISTA, Windows 7.



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

## SPECIFICATIONS

|                  |   |                                                                      |
|------------------|---|----------------------------------------------------------------------|
| CPU              | : | Intel Core 2 Quad/Duo, Celeron 400 serien. LGA775 sokkel             |
| Chipset          | : | Intel Q35 / ICH9                                                     |
| Digital I/O      | : | 4 indgange og 4 udgange (TTL)                                        |
| USB              | : | 4 x USB 2.0 (Hi-Speed)                                               |
| Driftstemperatur | : | 0 - 60o C ved 10 - 90 % ikke-kondenserende luftfugtighed             |
| BIOS             | : | 4 Mbit Award flash BIOS med ACPI understøttelse                      |
| Drev             | : | 1 x ATA/66/100/133, 4 x SATA300                                      |
| FSB              | : | 800/1066/1333 MHz                                                    |
| Grafik           | : | Integreret Intel GMA3100 (1 x DB15HDF VGA-stik)                      |
| Hukommelse       | : | 2 x 240-pin (dual channel) DDR2 maks. 4 GB, PC2-5400/6400            |
| Interface        | : | 1 x FDD diskettecontroller til to 3½" eller 5¼" drev (maks. 2,88 MB) |
| Lyd              | : | ICH9 AC97 Codec                                                      |



## SPECIFICATIONS

|                |   |                                                                       |
|----------------|---|-----------------------------------------------------------------------|
| Overvågning    | : | System/CPU - temperatur og - spænding                                 |
| Porte          | : | 1 x SPP/EPP/ECP, bi-direktionel, med 1 x DB25F-stik                   |
| Porte          | : | 1 x RS232 (DB9M), 1 x RS232/422/485 (DB9M)                            |
| RAID niveau    | : | PICMG 1.3 (PCI Express)                                               |
| Strømforsyning | : | Via PICMG bussen og ATX 12V stik (Se kapitel 19 for strømforsyninger) |
| Tastatur/mus   | : | 2 x mini-DIN6 PS/2 via Y-splitterkabel (medfølger)                    |
| Watchdog       | : | Op til 255 sekunders timeout                                          |

