

## 15" panel PC 6. generasjons i3 / i5 (ekstrautstyr) prosessor med Touch IP66 front

### FEATURES

- Bygg på bestilling
- 15" TFT-LCD
- CPU i3 (i5-alternativ)
- Maks. res. 1024 x 768
- Berøringsprojisert Kapasitiv berøring
- 4 GB DDR4 RAM (maks. 16 GB)
- 2 x USB
- 2 x RJ45 Lan
- 1 x RS232/422/485, 1 x RS232
- IP65 foran
- OS-støtte: Win. Embedded Compact 7,  
Win 7/7 Pro, Win 7 Ultimate, Win Emb. 8.1 Industry  
Pro
- Windows 10 IoT



## SPECIFICATIONS

|                  |   |                                                                                                                                                          |
|------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU              | : | Onboard Intel 4th Gen. Core i3 CPU (option i5)                                                                                                           |
| USB              | : | 2 x USB 3.0 type A                                                                                                                                       |
| Driftstemperatur | : | temperature(°C) 0~50°C, -20~60°C (option)                                                                                                                |
| Annen            | : | Optioner: 2 x CAN 2 x USB 2.0 type A + 1 x Mini-PCle slot + 1xRS-232 DB-9 via TB-528C1U2P1, 2 x USB 2.0 type A , UPS battery 21W/10.8V/1.95Ah            |
| Ethernet         | : | 2 x GbE LAN RJ-45                                                                                                                                        |
| Forsyning        | : | DC 9~36V 1 x 3-pin DC Power input terminal / 1 x 2-Pin Power Switch                                                                                      |
| Hukommelse       | : | Onboard 4GB DDR4L / max 8GB                                                                                                                              |
| LCD              | : | 15" TFT-LCD Max. resolution 1024 x 768 Max. color 16.7M Luminance(cd/m²) 420 Viewangle(H°/V°) 160/160 Backlight lifetime(hrs) 50,000                     |
| Luftfugtighed    | : | 10 to 90%@ 40°C, non-condensing                                                                                                                          |
| Lyd              | : | 1 x Audio Line Out                                                                                                                                       |
| Montering        | : | Panel Mounting / VESA 100 x 100                                                                                                                          |
| OS SUPPORT       | : | Windows Embedded Compact 7, Windows Embedded Standard 7, Windows 7 Pro (FES) Windows 7 Ultimate (FES), Windows Embedded 8.1 Industry Pro, Windows 10 IoT |



**DANBIT**

IPP15I3

## SPECIFICATIONS

Touch : Projected Capacitive Touch, USB

Dimensioner : 410mm x 310mm x 54.7mm



Danbit A/S Schous plass 1 Oslo, N-0552  
Norway



67 104 460



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.